TECHNICAL INFORMATION



COATERS

BARRAGLANZ





Art. No. 90.162.942 10 L canister

- high quality and hard wearing coater
- for all water resistant floor coverings also for sealed wood and parquet floors
- excellent leveling and good pore filling properties
- safe step
- can be high speed polished
- ideal partner for surface restauration in combination with Solex system dry spray basic cleaner
- resistant to surface disinfection limited as to restancy of hand-disinfection agents

APPLICATION RANGE:

For hard wear coating of porous and sealed surfaces. Optimum surface protection of cautchouque, pvc, lino, wood and parquet, for laminates, natural and artificial stone, epoxy and hart as well as industrial floors, refer to chart.

INSTRUCTIONS FOR USE AND DOSAGE:

Apply Barraglanz only on basic cleaned floor surface. Highly porous surfaces - such as lino - it is recommended to use a good quality sealer - for instance Polymer Primer - or Barraglanz in a dilution of 1:1 - 1 part product - 1 part water. After the first coating - allow time to dry properly. Use single disk machine and relevant pad and work over the first sealed level - before coating. Turn off heaters. Ventilate rooms well. Apply Barraglanz in 3 thin layers. Allow each layer to dry for ca. 20-30 minutes.

Product consumption ca. 12.5-25 ml/m² and layer. After completion - allow for 2 hours settling time - before walking. Coater will still mature during one week - therefore do not high speed. After this time - high speed processing will compact the coating - and will balance Barraglanz.

In case of **surface maintenance** Barraglanz may be used in a 1:1 - 1:10 dilution - for cleaning off soilage and for maintenance wiping the surface. Use a fresh mop and work in the Figure-8 Wiping Technology.

For spray buffing - use coater in a 1:1 dilution. For surface restauration and basic cleaning we recommend to use Solex, Lin Compact, Power Strip Neutra, Agil.

For maintenance cleaning – we recommend to use Blue Star, Premium N° 4, Kleen Top or Prodomo Clear Wipe-And-Care.

Protect against freezing temperatures!

TECHNICAL DATA:

Form:	milky white liquid
Odour:	
Viscosity:	low
Density:	1026 g/L
pH-value in delivery state:	

INGREDIENTS:

Below 5 %:	anionic surfactants	
Contains:	preservatives	
GISCODE:	GE 10	
Stability:	at least 1 year in original containers, protect against frost	
The surfactants contained in this preparation comply with the biodegradability criteria as laid		
down in Regulation (EC) No. 648/2004 on detergents.		

LABELLING: not applicable

According to EC-regulations or the corresponding national regulations the product does not have to be labelled.

TRANSPORT:

No dangerous good in sense of these transport regulations (ADR).

KLEEN PURGATIS GmbH

Dieselstraβe 10 D-32120 Hiddenhausen Fon +49 (0) 5223 9970-40 Fax +49 (0) 5223 9970-195 info@kleen-purgatis.de www.kleen-purgatis.de

An Affiliated Company of the BUDICH GROUP

Sales Department International:

KLEEN PURGATIS International AG

Firststrasse 30A CH-8835 Feusisberg Fon +41 (0) 44 515 35 60 Fax +41 (0) 44 515 35 69 info@kleen-purgatis.ch

www.kleen-purgatis.com