

SAFETY DATA SHEET

in accordance with Commission Regulation (EU) No. 1907/2006

Page: 1

Compilation date: 30.08.2010

Revision date: 25.09.2015

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: KLEEN PRO PICCOMAT DC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Workshop Cleaner for machine application for professional users

1.3. Details of the supplier of the safety data sheet

Company name: KLEEN PURGATIS GmbH

Dieselstraße 10

D - 32120 Hiddenhausen

Deutschland

Tel: +49 (0)5223 - 9970-40

Fax: +49 (0)5223 - 9970-50

Email: info@kleen-purgatis.de

1.4. Emergency telephone number

Emergency tel: +49 (0)551 - 19240 (GIZ-Nord)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1A: H314

Most important adverse effects: Causes severe skin burns and eye damage.

*2.2. Label elements

Label elements under CLP:

Hazard statements: H314: Causes severe skin burns and eye damage.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion



Hazard components for labelling: Sodium hydroxide, Potassium triphosphate

Precautionary statements: P102: Keep out of reach of children.

P280: Wear protective gloves/eye protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water/shower.

[cont...]

SAFETY DATA SHEET

KLEEN PRO PICCOMAT DC

Page: 2

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P309+311: IF exposed or if you feel unwell: Call a POISON CENTER or doctor.

2.3. Other hazards

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

POTASSIUM TRIPOLYPHOSPHATE - REACH registered number(s): -

EINECS	CAS	CLP Classification	Percent
237-574-9	13845-36-8	Met. Corr. 1: H290; Skin Irrit. 2: H315; Eye Irrit. 2: H319	5-10%

SODIUM CUMENESULFONATE - REACH registered number(s): -

EINECS	CAS	CLP Classification	Percent
248-983-7	28348-53-0	Eye Irrit. 2: H319	1-5%

FATTY ALCOHOL ALCOXYLATE - REACH registered number(s): -

EINECS	CAS	CLP Classification	Percent
-	120313-48-6	Skin Irrit. 2: H315; Eye Dam. 1: H318; Aquatic Acute 1: H400; Aquatic Chronic 2: H411	1-2.5%

SODIUM HYDROXIDE -REACH registered number(s): 01-2119457892-27-0000

EINECS	CAS	CLP Classification	Percent
215-185-5	1310-73-2	Skin Corr. 1A: H314	<1%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a physician if problems persist.

Inhalation: Provide fresh air. In case of respiratory tract irritation, consult a physician.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact. Blistering may occur.

Eye contact: There may be irritation and pain. Corneal burns may occur.

Ingestion: Nausea and stomach pain may occur. Corrosive burns may appear around the lips.

Inhalation: Not applicable.

Delayed / immediate effects: Immediate effects can be expected after long-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

[cont...]

SAFETY DATA SHEET

KLEEN PRO PICCOMAT DC

Page: 3

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive.

5.3. Advice for fire-fighters

Advice for fire-fighters: not necessary. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Dilute with water.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Wash with plenty of water. Ventilate affected area. Refer to section 13 of SDS for suitable method of disposal.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: No special measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Keep away from food, drink and animal feedingstuffs. Storage class: 8B (Non-combustible corrosive substances)

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): GISCODE: GG70

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

[cont...]

SAFETY DATA SHEET

KLEEN PRO PICCOMAT DC

Page: 4

SODIUM HYDROXIDE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	2 mg/m ³	-	-

8.2. Exposure controls

Engineering measures: Ensure storage room has retention walls.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves. Suitable material: NR (natural rubber), CR (polychloroprene) or NBR (nitrile rubber), category III according to EN 374. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Breakthrough time (maximal wear duration): Wear duration with occasional contact, splashes (Level 2: < 30 min): Disposable-gloves, Thickness of the material 0,1mm. Wear duration with permanent contact (Level 6: < 480min): Protective gloves, Thickness of the glove material 0,7 mm. Breakthrough times and swelling properties of the material must be taken into consideration.

Eye protection: Tightly fitting safety goggles.

Skin protection: Not applicable.

Environmental: No special requirement.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow-green

Odour: fresh

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Miscible

Relative density: 1,087 g/ml

pH: 14

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

[cont...]

SAFETY DATA SHEET

KLEEN PRO PICCOMAT DC

Page: 5

10.4. Conditions to avoid

Conditions to avoid: No hazardous decomposition products if stored and handled as prescribed.

10.5. Incompatible materials

Materials to avoid: None known

10.6. Hazardous decomposition products

Haz. decomp. products: No hazardous decomposition products known.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
KTPP: ORL	RAT	LD50	>2000	mg/kg
Fatty alcohol ethoxylate: ORL	RAT	LD50	>2000	mg/kg

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact. Blistering may occur.

Eye contact: There may be irritation and pain. Corneal burns may occur.

Ingestion: Nausea and stomach pain may occur. Corrosive burns may appear around the lips.

Inhalation: Not applicable.

Delayed / immediate effects: Immediate effects can be expected after long-term exposure.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
KTPP: Leuciscus idus	48H LC0	ca. 800	mg/l
Leuciscus idus	96H LC50	1-10	mg/l
Fatty alcohol ethoxylate: Water plants	72H EC50	0,1-1	mg/l

12.2. Persistence and degradability

Persistence and degradability: The surfactant(s) contained in this preparation complies with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: no data available.

[cont...]

SAFETY DATA SHEET

KLEEN PRO PICCOMAT DC

Page: 6

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: The product has not been tested. Data apply to the components with the highest toxicological risk.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Dispose of waste according to applicable local, state and federal regulations.

Waste code number: 20 01 29

Disposal of packaging: May be reused following decontamination.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1719

14.2. UN proper shipping name

Shipping name: CAUSTIC ALKALI LIQUID, N.O.S.

LQ: 5l

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

[cont...]

SAFETY DATA SHEET

KLEEN PRO PICCOMAT DC

Page: 7

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No. 1907/2006.

* indicates text in the SDS which has changed since the last revision.

Data references: Safety data sheets from our raw material suppliers

Department issuing MSDS: Product Development Department;

Contact: Ms. Tiemann, Ms. Klumpe

Classification for mixtures and used evaluation method according to article 9 of regulation (EC) 1272/2008 [CLP]: extreme pH value

Phrases used in s.2 and 3: H290: May be corrosive to metals.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.