

TECHNICAL INFORMATION

KLEEN
PURGATIS

COATERS

SUPER LASTIC METALLIC



Art. No. 162.822 10 L Canister

- hard wearing coater based on a cross-linked polymer dispersion, for high speed polishing
- high value basis and hard wear coater for all water resistant and basic cleaned floor coverings
- safe step features, good and longterm stability
- good leveling, high gloss
- high rate of solids contained in product
- ideal partner for floor surface restoration in combination with Solex system dry basic cleaner

APPLICATION RANGE:

Super Lastic Metallic is recommended for coating of PVC; stone, hard- and industrial floors. Ideal for application on highly stressed floors in rooms with high rate of public visitors/ persons and for high rate of soilage accumulation.

INSTRUCTIONS FOR USE AND DOSAGE:

Principally Super Lastic Metallic will be applied to properly basic cleaned and dried floor coverings. On strong porous floor coverings - such as **linoleum** - it is recommended to use a polymer primer prior to coating. After the application of the primer - and after drying time - use single disk machine and level this sealed surface. Turn down heat sources and air rooms well. Then apply Super Lastic Metallic in 1-3 layers. Each layer should be given ca. 30 min. time for proper drying. Product consumption: ca. 12.5-25 ml/m² and layering. Allow 2 hrs to dry - before walking on coated floor surface. Allow 24 hrs. to settle and mature - before stressing coated surface. Super Lastic Metallic will mature in the following 7 days - and then can be high speed polished. Polishing will compact the coater! **Buffing** - use coater in a dilution of 1:1. For **floor restoration** or for **basic cleaning** we recommend to use Solex, Agil, Lin Compact, Power Strip, or RZ-ST 10. For **daily cleaning** and maintenance we recommend Blue Star, Premium N^o 4, Kleen Top or Prodomo Clear Wipe and Shine. Do **not** use directly on PU protected floor coverings.

If improperly applied - and for claims resulting from such improper handling - there will be no legal claims accepted.

TECHNICAL DATA:

Form: milky white liquid
Odour: product specific
Viscosity: low
Density: 1030 g/l
pH-Value in delivery state: 9

INGREDIENTS:

Below 5 %: anionic surfactants
Contains: preservatives: BENZISOTHIAZOLINONE
Giscode: GE 10
Stability: at least one year in original containers, protect against frost and heating

LABELLING: not applicable

According to EC-regulations or the corresponding national regulations the product does not have to be labelled.

TRANSPORT:

No dangerous good in sense of these transport regulations (ADR).

Made in
Germany

KLEEN PURGATIS GmbH

Headquarters

Dieselstraße 10
D-32120 Hiddenhausen
Fon +49 (0) 5223 9970-40
Fax +49 (0) 5223 9970-50
info@kleen-purgatis.de

Sales Department International

Firststrasse 15
CH-8835 Feusisberg
Fon +41 (0) 44 515 35 61
Fax +41 (0) 44 515 35 69
info@kleen-purgatis.ch

www.kleen-purgatis.de

An Affiliated Company
of the BUDICH GROUP