TECHNICAL INFORMATION



BASIC AND INDUSTRIAL CLEANSER

RZ-ST 10





Art. No. 600.982 10-I-canister

- for the thorough cleaning of all alkali and water-resistant types of floor covering, such as PVC, CV, natural and artificial stone
- neutralisation unnecessary
- removes fat, oil and rust residues effortlessly
- even removes layers of plastic dispersions, polymer coatings and wax films easily and thoroughly
- low froth, suitable for use in automatic and high pressure cleaners
- not suitable for rubber, linoleum and asphalt surfaces

INSTRUCTIONS FOR USE AND DOSAGE:

Apply generously, diluted 1:1 to 1:10 with cold water, according to the type of coating or encrusting and allow it to work for approx. 10-15 minutes. A dilution of up to 1:200 is possible in the case of fat soiling, e.g. in the industrial sector and the sector of large kitchens. Work the floor with a pad or a brush, if necessary. Remove the loosened dirt subsequently. Simply rinse the surface thoroughly with clear water, in order to avoid incrustations.

Please see related product information for further information. Only use according to instructions and store out of reach of children.

TECHNICAL DATA:

Form:	yellow liquid
Odour:	
Viscosity:	,
Density:	1040 g/L
pH-value in delivery state:	

INGREDIENTS:

Below 5 %:	non-ionic-surfactants, soap, phosphonates
Giscode:	GG 90
Stability:	at least one year in original containers

LABELLING:



Danger

Contains Disodium metasilicate.

Hazard statements: H314: Causes severe skin burns and eye damage. Contains triisobutylphosphat. May produce an allergic reaction. Precautionary statements: P102: Keep out of reach of children. P280: Wear protective gloves/eye protection. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water/shower. P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P310: Immediately call a POISON CENTER or doctor.

TRANSPORT: UN number: 1719 / Shipping name: CAUSTIC ALKALI LIQUID, N.O.S. (Disodium metasilicate) LQ: 5L / Transport class: 8 / Packing group: III / ADR.

KLEEN PURGATIS GmbH

Zentrale

Dieselstraße 10 D-32120 Hiddenhausen Fon +49 (0) 5223 9970-40 Fax +49 (0) 5223 9970-50 info@kleen-purgatis.de

Vertrieb International

Firststrasse 15 CH-8835 Feusisberg Fon +41 (0) 44 515 35 61 Fax +41 (0) 44 515 35 69 info@kleen-purgatis.ch

www.kleen-purgatis.de

Ein Unternehmen der BUDICH GRUPPE